Safety Data Sheet **TRANSPROTEC 700**



1. Identification	
Product identifier	TRANSPROTEC 700
Product code	1106
Other means of identification	None.
Recommended use of the chemical and restrictions on use	Antirust and protection against corrosion. Not recommended for any other use not detailed on product data sheet or label.
Emergency phone number	Quebec Poison Center: 1-800-463-5060 (toll free in QC) Ontario and Manitoba Poison Centres: 1-800-268-9017 or 419-813-5900 BC Drug and Poison Information Centre: 1-800-567-8911 (toll free in BC) or contact your local poison control centre in the state/province or territory where you live. Canutec: 613-996-6666 (for transportation)

2. Hazard identification

Summary

Avoid contact with skin, eyes and clothing. Avoid prolonged or repeated inhalation of mist or vapor. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.

WHMIS 2015/GHS/OSHA HCS 2012

Eye irritation (Category 2B)

WARNING

H320: Causes eye irritation

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P264: Wash face, hands and any exposed skin thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye protection.

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P363: Wash contaminated clothing before reuse.

P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice or attention.

3. Composition/information on ingredients			
Common name	CAS	Weight % content	
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	10 - 90 %	
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	10 - 90 %	
Residual oils (petroleum), solvent-refined	64742-01-4	10 - 90 %	
Propylene Carbonate	108-32-7	0.5 - 1.5 %	

Note: The product is made at 99.9% of a mixture of these highly refined ingredients, containing no polycyclic aromatic hydrocarbon (PAH).

4. First-aid	measures
Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. If a problem develops or persists, seek medical attention.
Eye contact	Flush with water for at least 15 minutes. Remove contact lenses if easy to do. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with plenty of water. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause redness and irritation to eyes.
Notes to the physician	If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures		
Suitable extinguishing media	Dry chemicals, chemical foam, carbon dioxide (CO2). Do not use a heavy water jet.	
Specific hazards arising from the chemical	Non-flammable. May be combustible at high temperature.	
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.	
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.	

6. Accidental release measures		
	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.	

	Prevent entry into sewers, closed areas and release to the environment. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Ventilate the area well. Remove sources of ignition. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Dispose via a licensed waste disposal contractor.

7. Handling and storage		
Precautions for safe handling	Use in well ventilated area. Avoid contact with eyes. Avoid prolonged contact with skin. Avoid prolonged or repeated breathing of vapours or mists. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Avoid contamination with another chemical product. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. After use, wash hands with soap and water. Wash contaminated clothing before reuse.	
Conditions for safe storage, including any incompatibilities	Store tightly close and in properly labelled container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from incompatible materials (see section 10). Keep away from direct sunlight and heat.	
Storage temperature	10 to 45°C (50 to 113°F)	

Dangerous to Life or Health Distillates (petroleum), hyd Distillates (petroleum), soli Residual oils (petroleum), Appropriate engineering controls		STEL TWA (8h) TWA (8h) TWA (8h)	Mist Mist Mist	10 mg/m ³ 1 mg/m ³	NIOSH
Distillates (petroleum), sol Residual oils (petroleum), Appropriate engineering controls	olvent-refined heavy paraffinic , solvent-refined	TWA (8h)	Mist	•	
engineering controls	Provide sufficient mechanical	I VVA (OII)	Mist Mist	5 mg/m ³ 5 mg/m ³ 5 mg/m ³	BC ACGIH , NIOSH, ON, OSHA, RSST ACGIH , OSHA, RSST ACGIH , ON, OSHA, RSST
Individual protection me		Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
• · · · · · · · · · · · · · · · · · · ·	easures				
Eye	Wear safety glasses. If there is a risk of contact with eyes, wear chemical splash goggles.				
	If any risk of skin contact wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.				
3	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. To clean up a spill, if necessary, wear a synthetic polyethylene coveralls manufactured to provide protection against liquid chemical.				
	A respirator is not required in a well-ventilated area. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.				
Feet	a full face respirator mask with			ar ir raiging arriva	1 100 IIIL U 15.



9. Physical and chemical properties				
Physical state	Semi-solid (Grease)	Flammability	Non-flammable	
Colour	Amber or black	Flammability limits	N/Av.	
Odour	Characteristic	Flash point	N/Av.	
Odour threshold	100 ppm	Auto-ignition temperature	>350°C (662°F)	
рН	N/Ap.	Sensibility to electrostatic charges	N.Av.	
Melting point	-10°C (14°F)	Sensibility to sparks and/or friction	No	
Freezing point	-10°C (14°F)	Vapour density	>1 (Air = 1)	
Boiling point	150 to 600°C (302 to 1112°F)	Relative density	0.9 kg/L (Water = 1)	
Solubility	Insoluble in water.	Partition coefficient n-octanol/water	N/Av.	
Evaporation rate	< Butyl Acetate	Decomposition temperature	N/Av.	
Vapour pressure	<1kPa (7.5 mm Hg) @ 25°C (77°F)	Viscosity	>20.6 cSt @ 40°C (104°F)	
Percent Volatile	N/Av.	Molecular mass	N/Ap.	
N/Av.: Not Available N/Ap.: Not Applicable Und.: Undetermined N/E: Not Established				

10. Stability and reactivity	
Reactivity	No known dangerous reactions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	Hazardous polymerization will not occur.
Conditions to avoid	Avoid contact with incompatible materials.
Incompatible materials	Strong oxidizing agents (e.g. chlorine, fluorine, nitric acid, perchloric acid, peroxides, nitrates, chlorates, chromates, permanganates and perchlorates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicolo	ogical informati	ion		
Numerical measures of toxicity), hydrotreated heavy paraffinic), solvent-refined heavy paraffinic	Ingestion >15000 mg/kg Rat LD50 Skin >5000 mg/kg Rabbit LD50 Ingestion >5000 mg/kg Rat LD50 Inhalation 2.18 mg/l/4h Rat LC50	
	Residual oils (petroleum), solvent-refined		Skin >5000 mg/kg Rabbit LD50 Ingestion >5000 mg/kg Rat LD50 Inhalation 2.18 mg/l/4h Rat LC50 Skin >5000 mg/kg Rabbit LD50	
	Propylene Carbonate	•	Ingestion >29000 mg/kg Rat LD50 Inhalation >5 mg/l/4h Rat LC50 Skin >20000 mg/kg Rabbit LD50	
Likely routes of exposure	Skin, eyes, inhalation, ingestion.			
Delayed, immediate and chronic effects	Eye contact	May cause redness and irritation to eyes. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.		
	Skin contact Prolonged or repeated contact may cause defatting dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404): tests performed with each ir mixture gave not irritating to slightly irritating results.			
	Inhalation	greatly minimize the potential for	nly and following basic precautionary measures will harmful exposure to this product under normal use centrations of vapor from heated product may cause	
	Ingestion	Low degree of acute toxicity. Swaresulting in nausea, vomiting, cra	allowing will causes digestive tract disturbances mps and diarrhea.	
	Respiratory or skin Ingredients present at levels greater than or equal to 0.1% of this product are sensitization or respiratory sensitizers. IARC/NTP No ingredients listed.			
	Classification			
	Carcinogenicity The following information has been reported for the aliphatic petroleum disti regards to carcinogenicity (IARC, 1987): Untreated and mildly-treated oils at carcinogenic to humans (Group 1), and highly-refined oils are not classified carcinogenic to humans. Ingredients present at levels greater than or equal this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP o			
	Mutagenicity	Ingredients in this product present known to cause mutagenic effect	It at levels greater than or equal to 0.1% are not s.	
	Reproductive toxicity	known to cause reproduction effe	at levels greater than or equal to 0.1% are not ects.	
	Specific target organ toxicity - single exposure	No target organ is listed.		
	Specific target organ toxicity - repeated exposure	No target organ is listed.		
Interactive effects	No information availa	ble.		
Other information			mixture were calculated to be greater than 2000 HMIS 2015 and OSHA HCS 2012.	

12. Ecologic	eal information	
Ecological toxicity	Fish, various LC50 SES / NES Aquatic Invertebrates, various EC50 SES / NES Aquatic Plant - various EC50 SES / NES	
Persistence	Moderately persistent in the environment.	
Degradability	Biodegradable (<30% in 28 days). The product is a heavy hydrocarbon mixture in which some ingredients are not readily biodegradable (OECD 301B, IUCLID).	
Bioaccumulative potential	Log Kow values ranging from about 5 to 25. Bioconcentration Factor (BCF) between 0.9 and 750000 for the mixture. These values indicate a high degree of bioaccumulation.	
Mobility in soil	Insoluble in water. This mixture is likely to have high Koc values (>5000), indicating a high degree of sorption to the organic matter in soils. This value suggests that some components will display low mobility and some will be essentially immobile in soil. This product pollutes water and contaminates the soil.	
Other adverse effects	Due to the very low solubility of these chemicals in water, the acute toxicity to fish and aquatic invertebrates, and the toxicity to aquatic plants are considered to be no effects at saturation (NES). The chronic toxicity to aquatic invertebrates is also considered to be no effects at saturation (NES). This chemical does not deplete the ozone layer.	

13. Disposal considerations

Container

Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Non-use oils or waste oils can be reprocessed (recycle) where there is a recovery program. Waste oils should be classified as hazardous mixtures. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.

14. Transport information						
UN Number	UN					
UN Proper Shipping Name	Not regulated by TDG (Canada) and 49 CFR DOT (USA).					
Environmental hazards	This material is not listed as a marine pollutant.					
Special precautions for user	No information available for this product.					
TDG - Transportation o	f Dangerous Goods (Canada)					
Transport hazard class(es)	Not regulated					
Packing group	Not regulated					
Emergency response guidebook 2016						
IMO/IMDG - Internation	al Maritime Transport					
Classification	Not regulated					
IATA - International Air Transport Association						
Classification	Not regulated					
These transportation classifications	are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper					

transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4		X		
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7		X		
Residual oils (petroleum), solvent-refined	64742-01-4		X		
Propylene Carbonate	108-32-7		Х		

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	X								
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	X								
Residual oils (petroleum), solvent-refined	64742-01-4	X								
Propylene Carbonate	108-32-7	Х				Х				

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act List of Hazardous Substances
- CWA Priority: Clean Water Act Priority Pollutant list

California Proposition 65

No ingredients listed.

Other regulations





16. Other in	formation
Date (YYYY-MM-DD)	PRODUITS LUBRI-DELTA INC. 2016-11-02
Version	01
Other information	- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php - High Production Volume (HPV) Chemical Challenge Program, U.S. EPA, http://www.epa.gov/hpv/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca - OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, http://webnet.oecd.org/HPV/UI/Search.aspx - The National Center for Biotechnology Information, National Institutes of Health (NIH), U.S. National Library of Medicine, www.ncbi.nlm.nih.gov
	ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System
	To the best of our knowledge, the information contained herein is accurate. However, neither Prī¿½ventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.