



Safety Data Sheet

Issue Date: 21-May-2013

Revision Date: 07-Aug-2014

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Coastal Premium Moly EP Grease

Other means of identification

SDS # WUI-050

Recommended use of the chemical and restrictions on use

Recommended Use Lubricating grease.

Details of the supplier of the safety data sheet

Supplier Address

Warren Oil Company, LLC
915 E. Jefferson Ave.
West Memphis, AR 72301

Emergency Telephone Number

Company Phone Number 1-800-428-9284
Emergency Telephone (24 hr) CHEMTREC 1-800-424-9300

2. HAZARDS IDENTIFICATION

Appearance Dark gray to black semi-solid to solid

Physical State Semi-solid to solid

Odor Mild petroleum

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

Signal Word

Warning

Hazard Statements

Harmful if inhaled
Causes skin irritation
Causes serious eye irritation



Precautionary Statements - Prevention

Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell

Other Hazards

Harmful to aquatic life with long lasting effects

Unknown Acute Toxicity

16.05% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Severely Hydrotreated Heavy Naphthenic Petroleum Oil	64742-52-5	60-70
Residual oils (petroleum), solvent refined	64742-01-4	20-30
Zinc Alkyl Dithiophosphate	68649-42-3	1-10
Lithium Hydroxide Solution	1310-66-3	1-10
Mineral Oil	64741-88-4	<1
Crystalline silica	14808-60-7	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures**General Advice**

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to the section on Exposure Controls and Personal Protection.

Eye Contact

Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness or pain persists.

Skin Contact

If burned by hot material, cool skin by quenching with large amounts of cool water. For contact with product at ambient temperatures, remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with mild soap and water. Seek medical attention if tissue appears damaged or if pain or irritation persists. Thoroughly clean contaminated clothing before reuse. Clean or discard contaminated leather goods. If material is injected under the skin, seek medical attention immediately.

Inhalation

Vaporization is not expected at ambient temperatures. This material is not expected to cause inhalation-related disorders under anticipated conditions of use. In case of overexposure, move the person to fresh air.

Ingestion

Do not induce vomiting unless directed to by a physician. Rinse out mouth with water. Never give anything by mouth to a person who is not fully conscious. Allow small quantities to pass through the digestive system. If large amounts are swallowed or irritation of discomfort, seek medical attention immediately.

Most important symptoms and effects**Symptoms**

Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Skin: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal. Ingestion: Check for possible bowel obstruction with ingestion of large quantities of material.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use dry chemical, foam, carbon dioxide or water fog.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Molten material can form flaming droplets if ignited. Water or foam may cause frothing. Use of water on product above 100°C (212°F) can cause product to expand with explosive force.

Hazardous Combustion Products Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/ or nitrogen.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight the fire from a safe distance in a protected location. Open any masses with a water stream to prevent re-ignition due to smoldering. Cool surface with water fog. Do not allow liquid runoff to enter sewers or public waters. Use caution when applying carbon dioxide or inert gas in confined spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal Precautions**

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Slipping hazard; do not walk through spilled material.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up**Methods for Containment**

Stop leak if you can do it without risk.

Methods for Clean-Up

For small spills, absorb or cover with dry earth, sand or other inert non-combustible absorbent material and place into waste containers for lateral disposal. Contain large spills to maximize product recovery or disposal. In urban areas, clean up spill as soon as possible. In natural environments, seek clean up advice from specialists to minimize physical habitat damage.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

If this product is stored or applied in high-pressure systems such as grease guns or hydraulic lines, there is the potential for accidental injection into the skin and underlying tissues. Empty containers may contain product residue that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store only in approved containers. Do not store with strong oxidizing agents. Do not store at elevated temperatures. Avoid storing product in direct sunlight for extended periods of time.

Incompatible Materials

Strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Severely Hydrotreated Heavy Naphthenic Petroleum Oil 64742-52-5	TWA: 5 mg/m ³ (oil mist) STEL: 10 mg/m ³ (oil mist)	TWA: 5mg/m ³ (oil mist) STEL: none estab.	TWA: none estab. STEL: none estab.
Molybdenum Disulfide 1317-33-5	TWA: 10 mg/m ³ Mo inhalable fraction TWA: 3 mg/m ³ Mo respirable fraction	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ Mo	IDLH: 5000 mg/m ³ Mo
Crystalline silica 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	(vacated) TWA: 0.1 mg/m ³ respirable dust : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust

Appropriate engineering controls

Engineering Controls

Ventilation controls are not normally required under anticipated conditions of use. Provide exhaust ventilation or other engineering controls if airborne mists or vapors concentrations exceed recommended occupational exposure limits listed. An eye wash station and safety shower should be located near work-station.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses equipped with side shields are recommended as a minimum protection in industrial settings. Wear goggles if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available.
Skin and Body Protection	None required for incidental contact. Use gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected. Use heat-protective gloves when handling product at elevated temperatures.
Respiratory Protection	The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Semi-solid to solid	Odor	Mild petroleum
Appearance	Dark gray to black semi-solid to solid	Odor Threshold	Not determined
Color	Dark gray to black		

<u>Property</u>	<u>NLGI Grade: 2 Thickener: Lithium</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	Not available	
Flash Point	150 °C / 302 °F	Open cup
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	No data	
Lower Flammability Limit	No data	
Vapor Pressure	<0.001 kPa (<0.01 mm Hg) (at 20°C)	
Vapor Density	>1	(Air=1)
Specific Gravity	0.91	(Water = 1)
Water Solubility	Negligible solubility in cold water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not available	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Not expected to occur.**Conditions to Avoid**

Keep away from extreme heat, sparks, open flame and incompatible materials.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/ or nitrogen.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information****Eye Contact** Causes serious eye irritation.**Skin Contact** Causes skin irritation.**Inhalation** Harmful if inhaled.**Ingestion** Do not ingest.**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Residual oils (petroleum), solvent refined 64742-01-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h
Mineral Oil 64741-88-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2.18 mg/L (Rat) 4 h
Molybdenum Disulfide 1317-33-5	-	-	> 2820 mg/m ³ (Rat) 4 h
Crystalline silica 14808-60-7	= 500 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects**Symptoms** Please see Section 4 of this SDS for symptoms.**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Carcinogenicity** Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder).**Numerical measures of toxicity**

Not determined

Unknown Acute Toxicity 16.05% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Severely Hydrotreated Heavy Naphthenic Petroleum Oil 64742-52-5		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Residual oils (petroleum), solvent refined 64742-01-4		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Zinc Alkyl Dithiophosphate 68649-42-3		1.0 - 5.0: 96 h Pimephales promelas mg/L LC50 static 10.0 - 35.0: 96 h Pimephales promelas mg/L LC50 semi-static		1 - 1.5: 48 h Daphnia magna mg/L EC50
Mineral Oil 64741-88-4		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Ammonium hydroxide 1336-21-6		8.2: 96 h Pimephales promelas mg/L LC50		0.66: 48 h water flea mg/L EC50 0.66: 48 h Daphnia pulex mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Zinc Alkyl Dithiophosphate 68649-42-3	Toxic

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT Not regulated
IATA Not regulated
IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA One or more ingredient(s) in this product is listed on the TSCA inventory

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

US Federal Regulations

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Zinc Alkyl Dithiophosphate - 68649-42-3	68649-42-3	1-10	1.0
Ammonium hydroxide - 1336-21-6	1336-21-6	<1	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc Alkyl Dithiophosphate 68649-42-3 (1-10)		X		

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Zinc Alkyl Dithiophosphate 68649-42-3	X		X
Lithium Hydroxide Solution 1310-66-3	X		
Molybdenum Disulfide 1317-33-5		X	
Crystalline silica 14808-60-7	X	X	X
Graphite 7782-42-5	X	X	X
Ammonium hydroxide 1336-21-6	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	Not determined

Issue Date: 21-May-2013
 Revision Date: 07-Aug-2014
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet