

# SAFETY DATA SHEET

Issue Date: 02-Sept.-2014

Revision Date: 02-April-2015

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Coastal Hi-Temp Grease

### Other means of identification

**SDS #** WUI-055

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lubricant.

### Details of the supplier of the safety data sheet

#### Supplier Address

Warren Oil Company, LLC  
915 E. Jefferson Ave.  
West Memphis, AR 72301

### Emergency Telephone Number

**Company Phone Number** 1-800-428-9284  
**Emergency Telephone (24 hr)** CHEMTREC 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**Appearance** Red semi-solid to solid      **Physical State** Semi-solid to solid      **Odor** Mild petroleum

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

### Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

### Signal Word

Warning

### Hazard Statements

Causes skin irritation  
Causes serious eye irritation



### Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash it before reuse

If skin irritation occurs: Get medical advice/attention

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Unknown Acute Toxicity**

11.163% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Severely Hydrotreated Heavy Naphthenic Petroleum Oil	64742-52-5	60-70
Residual oils (petroleum), solvent refined	64742-01-4	1-10
Antimony diamyldithiocarbamate	15890-25-2	1-10
Lithium Hydroxide Solution	1310-66-3	1-10

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

**First Aid Measures****General Advice**

If exposed or concerned: Get medical advice/attention. Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid.

**Eye Contact**

Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness or pain persists.

**Skin Contact**

If burned by hot material, cool skin by quenching with large amounts of cool water. For contact with product at ambient temperatures, remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with mild soap and water. Seek medical attention if tissue appears damaged or if pain or irritation persists. Thoroughly clean contaminated clothing before reuse. Clean or discard contaminated leather goods. If material is injected under the skin, seek medical attention immediately.

**Inhalation**

Vaporization is not expected at ambient temperatures. This material is not expected to cause inhalation-related disorders under anticipated conditions of use. In case of overexposure, move the person to fresh air.

**Ingestion**

Do not induce vomiting unless directed to by a physician. Rinse out mouth with water. Never give anything by mouth to a person who is not fully conscious. Allow small quantities to pass through the digestive system. If large amounts are swallowed or irritation of discomfort, seek medical attention immediately.

**Most important symptoms and effects****Symptoms**

May be harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician**

Skin: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal. Ingestion: Check for possible bowel obstruction with ingestion of large quantities of material.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use dry chemical, foam, carbon dioxide or water fog.

**Unsuitable Extinguishing Media** Not determined.

**Specific Hazards Arising from the Chemical**

Water or foam may cause frothing. Molten material can form flaming droplets if ignited. Use of water on product above 100°C (212°F) can cause product to expand with explosive force.

**Hazardous Combustion Products** Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/ or nitrogen.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Carbon dioxide and inert gas can displace oxygen. Use caution when applying carbon dioxide or inert gas in confined spaces. Fight the fire from a safe distance in a protected location. Open any masses with a water stream to prevent re-ignition due to smoldering. Cool surface with water fog. Do not allow liquid runoff to enter sewers or public waters.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to section 8. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Slipping hazard; do not walk through spilled material.

**Methods and material for containment and cleaning up****Methods for Containment**

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas.

**Methods for Clean-Up**

For small spills, absorb or cover with dry earth, sand or other inert non-combustible absorbent material and place into waste containers for lateral disposal. Contain large spills to maximize product recovery or disposal. In urban areas, clean up spill as soon as possible. In natural environments, seek clean up advice from specialists to minimize physical habitat damage.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Advice on Safe Handling**

If this product is stored or applied in high-pressure systems such as grease guns or hydraulic lines, there is the potential for accidental injection into the skin and underlying tissues. Empty containers may contain product residue that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

**Conditions for safe storage, including any incompatibilities**

<b>Storage Conditions</b>	Keep containers tightly closed in a dry, cool and well-ventilated place.
<b>Incompatible Materials</b>	Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Severely Hydrotreated Heavy Naphthenic Petroleum Oil 64742-52-5	TWA: 5 mg/m <sup>3</sup> (oil mist) STEL: 10 mg/m <sup>3</sup> (oil mist)	TWA: 5mg/m <sup>3</sup> (oil mist) STEL: none estab.	TWA: none estab. STEL: none estab.
Antimony diamyldithiocarbamate 15890-25-2	TWA: 0.5 mg/m <sup>3</sup> Sb	TWA: 0.5 mg/m <sup>3</sup> Sb (vacated) TWA: 0.5 mg/m <sup>3</sup> Sb	IDLH: 50 mg/m <sup>3</sup> Sb TWA: 0.5 mg/m <sup>3</sup> Sb
Barium Sulfonate 25619-56-1	TWA: 0.5 mg/m <sup>3</sup> Ba	TWA: 0.5 mg/m <sup>3</sup> Ba (vacated) TWA: 0.5 mg/m <sup>3</sup> Ba	TWA: 0.5 mg/m <sup>3</sup> except Barium sulfate Ba
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

**Appropriate engineering controls**

<b>Engineering Controls</b>	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
-----------------------------	--

**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and Body Protection</b>	Chemical resistant, impermeable gloves. Long sleeve shirt and long pants. Aprons. Wear a lab coat.
<b>Respiratory Protection</b>	Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical State</b>	Semi-solid to solid	<b>Odor</b>	Mild petroleum
<b>Appearance</b>	Red semi-solid to solid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Red		

<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>pH</b>	Not available	
<b>Melting Point/Freezing Point</b>	Not available	
<b>Boiling Point/Boiling Range</b>	Not available	
<b>Flash Point</b>	150 °C / 302 °F	Open cup
<b>Evaporation Rate</b>	Not available	
<b>Flammability (Solid, Gas)</b>	Not determined	
<b>Upper Flammability Limits</b>	Not available	
<b>Lower Flammability Limit</b>	Not available	
<b>Vapor Pressure</b>	<01001 kPA (<0.01 mm Hg)(at 20°C)	
<b>Vapor Density</b>	>10	(Air=1)
<b>Specific Gravity</b>	0.93	(Water = 1)
<b>Water Solubility</b>	Negligible	
<b>Solubility in other solvents</b>	Not determined	
<b>Partition Coefficient</b>	Not determined	
<b>Auto-ignition Temperature</b>	Not available	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	

## 10. STABILITY AND REACTIVITY

### **Reactivity**

Not reactive under normal conditions.

### **Chemical Stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**      Not expected to occur.

### **Conditions to Avoid**

Keep away from extreme heat, sparks, open flame and incompatible materials.

### **Incompatible Materials**

Strong oxidizing agents.

### **Hazardous Decomposition Products**

Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/ or nitrogen.

## 11. TOXICOLOGICAL INFORMATION

### **Information on likely routes of exposure**

#### **Product Information**

**Eye Contact**      Causes serious eye irritation.

**Skin Contact**      Causes skin irritation.

**Inhalation**      Do not inhale.

**Ingestion**      Do not ingest.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Lubricating oils (petroleum), hydrotreated spent 64742-58-1	> 2000 mg/kg ( Rat )	> 4480 mg/kg ( Rabbit )	-
Residual oils (petroleum), solvent refined 64742-01-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 2.18 mg/L ( Rat ) 4 h
Azelaic acid 123-99-9	> 5 g/kg ( Rat )	-	-
Xylene 1330-20-7	= 4300 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 47635 mg/L ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15354 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Information on physical, chemical and toxicological effects**

**Symptoms** Please see Section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

**Carcinogenicity** This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

**Numerical measures of toxicity**

Not determined

**Unknown Acute Toxicity** 11.163% of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Severely Hydrotreated Heavy Naphthenic Petroleum Oil 64742-52-5		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Lubricating oils (petroleum), hydrotreated spent 64742-58-1		79.6: 96 h Brachydanio rerio mg/L LC50 semi-static 3.2: 96 h Pimephales promelas mg/L LC50 semi-static		
Residual oils (petroleum), solvent refined 64742-01-4		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50

<p>Xylene 1330-20-7</p>		<p>13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static</p>	<p>EC50 = 0.0084 mg/L 24 h</p>	<p>3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50</p>
<p>Ethylbenzene 100-41-4</p>	<p>4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static</p>	<p>11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static</p>	<p>EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h</p>	<p>1.8 - 2.4: 48 h Daphnia magna mg/L EC50</p>

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Not determined

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Antimony diamylthiocarbamate 15890-25-2	Toxic

**14. TRANSPORT INFORMATION**

<b>Note</b>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
<b>DOT</b>	Not regulated
<b>IATA</b>	Not regulated
<b>IMDG</b>	Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Listed

**Legend:**  
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**US Federal Regulations**

**SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Antimony diamylthiocarbamate - 15890-25-2	15890-25-2	1-10	1.0
Barium Sulfonate - 25619-56-1	25619-56-1	<1	1.0
Xylene - 1330-20-7	1330-20-7	<1	1.0
Ethylbenzene - 100-41-4	100-41-4	<1	0.1

**CWA (Clean Water Act)**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Antimony diamylthiocarbamate 15890-25-2 ( 1-10 )		X		

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Antimony diamylthiocarbamate 15890-25-2	X		X
Lithium Hydroxide Solution 1310-66-3	X		



Barium Sulfonate 25619-56-1	X		X
Xylene 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	1	0	Not determined
<b>HMIS</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	1	1	0	Not determined

Issue Date: 05-Jun-2014  
 Revision Date: 2-April-2015  
 Revision Note: New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**